















> Product Overview Fuseholders

Type	Rated Voltage			Rated Current		Power Acceptance acc. IEC	Terminals					Approvals							
	Fuse-Link	IEC	UL	IEC	UL		Solder (THT)	Solder (SMD)	Quick-Connect	Screw	Rivet	VDE	VDE ÜG	NF	GAM T1	NNO	cURus	UR	CSA
PCB MOUNTING (THT)																			
 OGN Glow-wire resistant, cover optional	5 x 20	250 VAC	500 VAC 500 VDC	10 A	10 A	4 W / 10 A	•					•				•			
 OGD Glow-wire version and cover optional	5 x 20 6.3 x 32	500 VAC	600 VAC 600 VDC	10 A	16 A	4 W / 10 A	•					•	•			•			
 FPG5 Horizontal mounting, glow-wire version optional	5 x 20	250 VAC	400 VAC	10 A	16 A	2.5 W / 10 A	•					•				•			
 FAB Horizontal mounting, kicked or straight terminals	5 x 20	250 VAC	250 VAC	10 A	12 A	2 W / 10 A	•					•				•			
 FAS Horizontal mounting	5 x 20	250 VAC	-	6.3 A	-	1.6 W / 6.3 A	•					•							
 FBS2 Medical applications, shock-safe category PC3	5 x 20	250 VAC	250 VAC	10 A	10 A	2.5 W / 10 A	•					•				•			
 231409 Horizontal or vertical, AERO MIL MARINE	5 x 20	250 VAC 250 VDC	250 VAC 250 VDC	10 A	10 A	1.3 W / 10 A	•							•	•		•	•	
 FAU Horizontal mounting, kicked or straight terminals	5 x 20 6.3 x 32	250 VAC	250 VAC	10 A	16 A	2.5 W / 10 A 3.2 W / 10 A	•					•					•	•	
 FUP Horizontal mounting, high power applications	5 x 20 6.3 x 32	500 VAC	600 VAC 600 VDC	16 A	30 A	4 W / 16 A	•					•				•			
 FPG4 Vertical mounting, glow-wire version optional	5 x 20	250 VAC	400 VAC	10 A	16 A	2.5 W / 10 A	•					•				•			
 FAF Vertical mounting, IP54 optional	5 x 20	250 VAC	250 VAC	6.3 A	12 A	2 W / 6.3 A	•					•					•	•	
 FAP Vertical mounting	5 x 20	250 VAC	-	6.3 A	-	1.6 W / 6.3 A	•					•							
 FAC Vertical mounting, kicked or straight terminals	5 x 20 6.3 x 32	250 VAC	400 VAC	10 A	16 A	2.5 W / 10 A 3.2 W / 10 A	•					•					•	•	
 FUA Vertical mounting, high power applications	5 x 20 6.3 x 32	500 VAC	600 VAC 600 VDC	16 A	30 A	4 W / 16 A	•					•				•			










Product Overview Fuseholders

Type	Fuse-Link	Rated Voltage		Rated Current		Power Acceptance acc. IEC	Terminals					Approvals										
		IEC	UL	IEC	UL		Solder	Solder (THT)	Solder (SMD)	Quick-Connect	Screw	Rivet	VDE	VDE ÜG	NF	GAM T1	NNO	cURus	UR	CSA	KC	
PCB MOUNTING (THT)																						
 FMS (125V) Vertical mounting, for subminiature fuses	MSx 125	-	125 VAC 125 VDC	-	5 A	-		•														
 FMS (250V) Vertical mounting, for subminiature fuses	Mxx 250	-	250 VAC 250 VDC	-	6.3 A	-		•														
 FMR Horizontal mounting, for subminiature fuses	MSx 125	-	125 VAC 125 VDC	-	5 A	-		•														
 231787 THT fuseholder, 2 x 7 mm fuses	2 x 7	-	125 VAC 125 VDC	-	7 A	-		•											•	•		
PCB MOUNTING (SMD)																						
 FPG7 Horizontal mounting, glow-wire version optional	5 x 20	250 VAC	400 VAC	10 A	16 A	2.5 W / 10 A		•			•									•		
 OGN-SMD Glow-wire resistant, cover optional	5 x 20	250 VAC	500 VAC 500 VDC	10 A	10 A	4 W / 10 A		•			•									•		
 OGD-SMD Glow-wire version and cover optional	5 x 20 6.3 x 32	500 VAC	600 VAC 600 VDC	10 A	16 A	4 W / 10 A		•			•	•								•		
 OMH 125 Pre-assembled fuses optional, compact	OMx 63 Oxx 125	-	125 VAC	-	5 A	-		•												•	•	
 231786 SMD fuseholder, 2 x 7 mm fuses	2 x 7	-	125 VAC 125 VDC	-	7 A	-		•													•	•
PANEL MOUNTING																						
 FPG1 Screw mounting, front-side, IP67 optional	5 x 20	250 VAC	400 VAC	10 A	16 A	2.5 W / 10 A		•	•		•									•	•	
 FPG2 Screw mounting, rear-side, IP67 optional	5 x 20	250 VAC	400 VAC	10 A	16 A	2.5 W / 10 A		•	•		•									•	•	
 FPG3 Snap-in mounting, front-side	5 x 20	250 VAC	400 VAC	10 A	16 A	2.5 W / 10 A		•	•		•									•	•	
 FPG6 Press-fit mounting, front-side, IP67 optional	5 x 20	250 VAC	400 VAC	10 A	16 A	2.5 W / 10 A		•	•		•									•	•	
 FEF Fingergrip or slot cap, IP54 optional	5 x 20	250 VAC	250 VAC	10 A	10 A	4 W / 10 A		•			•									•	•	
 FEF (snap) Snap-in mounting, front-side	5 x 20	250 VAC	250 VAC	10 A	10 A	4 W / 10 A		•			•									•	•	
 FIN Screw mounting, front-side, IP67	5 x 20	250 VAC	250 VAC	10 A	10 A	2.5 W / 10 A		•	•		•									•	•	
 FIO Screw mounting, front-side, IP65 optional	5 x 20	250 VAC	250 VAC	10 A	10 A	2.5 W / 10 A		•	•		•									•	•	

Product Overview Fuseholders

Type	Fuse-Link	Rated Voltage		Rated Current		Power Acceptance acc. IEC	Terminals					Approvals							
		IEC	UL	IEC	UL		Solder (THT)	Solder (SMD)	Quick-Connect	Screw	Rivet	VDE	VDE ÜG	NF	GAM T1	NNO	cURus	UR	CSA
PANEL MOUNTING																			
 FIZ Screw mounting, front-side, IP67 optional	5 x 20	250 VAC	600 VAC 600 VDC	16 A	30 A	4 W / 16 A	•	•				•				•			
 FBS1 Medical applications, shock-safe category PC3	5 x 20	250 VAC	250 VAC	10 A	10 A	2.5 W / 10 A	•	•				•				•			
 23316P Screw mounting, AERO MIL MARINE	5 x 20	250 VAC	-	6.3 A	-	1.5 W / 6.3 A	•						•	•	•				
 231411 Screw mounting, AERO MIL MARINE	5 x 20	250 VAC	-	6.3 A	-	1.3 W / 6.3 A	•												
 FQE Optional black or red caps	5 x 20	250 VAC	-	6.3 A	-	2.5 W / 6.3 A	•												
 23312P Screw-cap, IP67 optional, AERO MIL MARINE	6.3 x 32	250 VAC	250 VAC	10 A	10 A	2.5 W / 10 A	•						•	•	•	•	•	•	•
 231549P Screw-cap, IP68, AERO MIL MARINE	6.3 x 32	250 VAC	-	16 A	-	3.6 W / 16 A	•						•	•					
 FEU Screw mounting, front-side	5 x 20 6.3 x 32	250 VAC	250 VAC	10 A	20 A	4 W / 10 A	•	•				•					•	•	
 FEU (Med) Medical applications, shock-safe category PC2	5 x 20 6.3 x 32	250 VAC	250 VAC	10 A	20 A	4 W / 10 A	•					•					•	•	
 FEU (Grip) Fingergrip screw-cap	5 x 20 6.3 x 32	250 VAC	250 VAC	10 A	20 A	4 W / 10 A	•					•					•	•	
 FEC Screw mounting, 3-phase applications	5 x 20 6.3 x 32	500 VAC	600 VAC 600 VDC	10 A	20 A	4 W / 10 A	•	•				•				•			
 FUL Screw mounting, 3-phase applications, optional IP67	5 x 20 6.3 x 32	500 VAC	600 VAC 600 VDC	16 A	30 A	4 W / 16 A	•	•				•				•			
 231600P AERO MIL MARINE, for special fuse size	4.7 x 16	250 VAC	-	5 A	-	1 W / 5 A	•								•	•			
 23530P Screw mounting, front-side, IP67 optional	10.3 x 38	-	600 VAC	-	25 A	4.5 W / 25 A		•							•	•	•		
SCREW OR RIVET MOUNTING																			
 UH Cover optional, 1 or 10 pole version	5 x 20	-	600 VAC 600 VDC	-	10 A	3.2 W / 10 A	•									•			
 UHB Cover optional	5 x 20	-	250 VAC	-	6.3 A	3.2 W / 4 A	•												
 OG (Holder) 5x20 Cover optional	5 x 20	-	600 VAC 600 VDC	-	10 A	2.5 W / 10 A	•									•			

Product Overview Fuseholders

Type	Fuse-Link	Rated Voltage		Rated Current		Power Acceptance acc. IEC	Terminals					Approvals								
		IEC	UL	IEC	UL		Solder	Solder (THT)	Solder (SMD)	Quick-Connect	Screw	Rivet	VDE	VDE ÜG	NF	GAM T1	NNO	cURus	UR	CSA
SCREW OR RIVET MOUNTING																				
 RSH 1 or 10 pole version	6.3 x 32	-	250 VAC	-	16 A	3.2 W / 10 A	•												•	•
 OG (Holder) 5x20 Screw or rivet mounting, THT	6.3 x 32	-	250 VAC	-	16 A	2.5 W / 10 A	•												•	•
IN-LINE MOUNTING																				
 FDI In-line mounting	5 x 20 6.3 x 32	32 VAC	-	6.3 A	-	2.5 W / 6.3 A	•													
DIN-RAIL MOUNTING																				
 FSO Solar / PV fuseholder, self-certified 1000 VDC	10.3 x 38	-	600 VAC 600 VDC	-	30 A	-				•									•	•
CLIPS																				
 OG (Clip) 5x20 Cover optional, kicked or straight terminals	5 x 20	-	500 VAC 500 VDC	-	6.3 A	-				•									•	
 OG (Clip) 5x20 / 6.3x32 For 5 x 20 or 6 x 32 fuses	5 x 20 6.3 x 32	-	600 VAC 600 VDC	-	16 A	-				•									•	
 CQP Heavy duty fuse clip, solar / PV applications	6.3 x 32	-	600 VAC 600 VDC	-	32 A	-				•									•	
 CSO Heavy duty fuse clip, solar / PV applications	10.3 x 38 10.3 x 85	-	1500 VAC 1500 VDC	-	32 A	-				•	•	•							•	
 231660 Solar / PV applications	10.3 x 38	-	-	-	20 A	-				•									•	

Information

Product specifications, such as ratings and approvals, may vary by product variant. Detailed and current information of the listed product types and its variants can be found on our website schurter.com/cp. Specifications are subject to change without notice.

Customized Solutions

In addition to its broad product range, SCHURTER also offers individual services to ensure all customer requirements. We will build specific samples and provide you with your customized solution.